

(19) World Intellectual Property  
Organization  
International Bureau



(43) International Publication Date  
12 February 2004 (12.02.2004)

PCT

(10) International Publication Number  
**WO 2004/013746 A2**

(51) International Patent Classification<sup>7</sup>: **G06F 3/033**

(21) International Application Number:  
PCT/IB2003/003243

(22) International Filing Date: 16 July 2003 (16.07.2003)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:  
02078156.3 1 August 2002 (01.08.2002) EP

(71) Applicant (for all designated States except US): **KONINKLIJKE PHILIPS ELECTRONICS N.V.** [NL/NL];  
Groenewoudseweg 1, NL-5621 BA Eindhoven (NL).

(72) Inventors; and

(75) Inventors/Applicants (for US only): **RAAP, Adriaan, Y.** [NL/NL]; Prof . Holstlaan 6, NL-5656 AA Eindhoven (NL). **JOHNSON, Mark, T.** [GB/NL]; Prof . Holstlaan 6, NL-5656 AA Eindhoven (NL). **DE BOER, Dirk, K., G.** [NL/NL]; Prof . Holstlaan 6, NL-5656 AA Eindhoven (NL).

(74) Agent: **RAAP, Adriaan, Y.**; Philips Intellectual Property & Standards, Prof. Holstlaan 6, NL-5656 AA Eindhoven (NL).

(81) Designated States (national): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU,

CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.


(84) Designated States (regional): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

#### Declaration under Rule 4.17:

— as to applicant's entitlement to apply for and be granted a patent (Rule 4.17(ii)) for the following designations AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, UZ, VC, VN, YU, ZA, ZM, ZW, ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE,

[Continued on next page]

(54) Title: TOUCH SENSITIVE DISPLAY DEVICE



(57) Abstract: A touch-sensitive display is made by incorporating a pressure dependent resistive polymer composite into the polymer networks, which are components of the electro-optical pixels. Examples are PDLC, electrophoretic displays, polymer dispersed guest/host systems and other polymer dispersed LC devices.

WO 2004/013746 A2

Rec'd PCT/PTO

01 FEB 2005

DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT,  
RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM,  
GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG)

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

**Published:**

- without international search report and to be republished upon receipt of that report

## Touch sensitive display device

The invention relates to a touch sensitive display device comprising an elastic (e.g. a polymer) structure with a multiple of picture elements and having means for applying driving voltages to said picture elements.

The display device is for instance a polymer dispersed liquid crystal display device. Liquid crystal display devices have found widespread use in the computer industry and in handheld devices ranging from mobile telephones and price tags to palm top computers and organizers. Also the combination with a touching device such as a stylus has found widespread applications, while also a need for ways of providing input via the display screen is felt.

USP 5,777,596 describes a touch sensitive liquid crystal display device that allows putting input into the associated device (e.g. a computer) by simply touching the display screen with a finger, a stylus or a pen. The device continuously compares the charge time of the liquid crystal display elements (picture elements) to a reference value and uses the result of the comparison to determine which elements are being touched.

One of the problems in said touch sensitive liquid crystal display device resides in restoring the right image after sensing. This is due to the fact that a blinking line is used which represents the switching of all picture elements in a row between two extreme states. When the blinking line reaches a certain row touching is detected by measuring the charging time of the picture elements. After measuring the picture elements are provided with adequate voltages to display the right image. In a similar way sensing by means of a blinking spot is disclosed in USP 5,777,596.

Such blinking however is visible on the display (artifacts)

Moreover, if a reflective display device is used, internal DC bias voltages may be present whereby charging differs for writing odd or even frames. In DC-driving methods (low power liquid crystal displays, electrophoretic displays) no inversion occurs so the method cannot be used at all there.

The problem of providing blinking signals can be overcome by making the spacing means (spacers) part of said means for monitoring the electrical characteristics of the picture elements. Said electrical characteristics may be capacitive, (non-linear) resistive or piezo-electric characteristics. However this will require structuring of e.g. the (non-linear) resistor into spacers with similar heights to ensure that electrical contact is created when the display is pressed since locally thinner spacers may not be pressed at all. Such processing will be complex, and touch sensing will not always be efficient at all points on the display.

The invention has among others as its goal to overcome these objections especially for display devices comprising a polymer structure.

It has as a further goal to introduce more functionality into the touch sensitive liquid crystal display device.

To this end in a touch sensitive display device according to the invention the elastic structure comprises touch sensitive elements while the touch sensitive display device has means for monitoring the electrical characteristics of said touch sensitive elements and sensing a change in said electrical characteristics.

By incorporating the polymer with pressure sensitive characteristics (e.g. non-linear resistivity such as may be realized by means of quantum tunneling composites) into the polymer network of the pixel, the pixel itself becomes intrinsically touch sensitive.

In this way the need for structured spacers is avoided, while the entire pixel area is touch sensitive, which increases the touch sensitivity and makes this touch sensitive display applicable for flexible and even wearable display applications.

In a further embodiment the means for monitoring the electrical characteristics of the touch sensitive elements comprise at least an electrode of a picture element.

The advantage of using the pixel itself as part of the touch sensitive element is that now the pixel electrodes can also be used for measuring the touch signal. In this way, no extra connections need to be made to the displays. Sensing can be carried out by simply identifying which row and column have been temporarily short-circuited by the touch pressure.

In a preferred embodiments the picture elements comprise at least one capsule containing an electro-optical medium. Examples are display devices based on liquid crystal – polymer composites like polymer-dispersed liquid crystal display devices, guest host systems, Axially Symmetric Mode liquid crystal display devices or electrophoretic displays while also electrochromic displays and displays based on electrowetting may be thought of.

These and other aspects of the invention are apparent from and will be elucidated with reference to the embodiments described hereinafter.

In the drawings:

Figure 1 schematically shows a touch sensitive (liquid crystal) display device,

Figures 2 and 3 show cross-sections of a part of a touch sensitive (liquid crystal) display device according to the invention.

The Figures are diagrammatic and not drawn to scale. Corresponding elements are generally denoted by the same reference numerals.

Figure 1 is an electric equivalent circuit diagram of a part of a touch sensitive display device 1 to which the invention is applicable. It comprises in one possible embodiment (one mode of driving, called the "passive mode") a matrix of pixels 8 defined by the areas of crossings of row or selection electrodes 7 and column or data electrodes 6. The row electrodes are consecutively selected by means of a row driver 4, while the column electrodes are provided with data via a data register 5. To this end, incoming data 2 are first processed, if necessary, in a processor 3. Mutual synchronization between the row driver 4 and the data register 5 takes place via drive lines 9.

In another possible embodiment (another mode of driving, called the "active mode") signals from the row driver 4 select the picture electrodes via thin-film transistors (TFTs) 10 whose gate electrodes are electrically connected to the row electrodes 7 and the source electrodes are electrically connected to the column electrodes. The signal which is present at the column electrode 6 is transferred via the TFT to a picture electrode of a pixel 8 coupled to the drain electrode. The other picture electrodes are connected to, for example, one (or more) common counter electrode(s). In Figure 1 only one thin-film transistor (TFT) 10 has been drawn, simply as an example.

Figure 2 shows a cross-section of a part of a touch sensitive liquid crystal device having a bottom substrate 11 and an upper substrate 12. The touch sensitive liquid crystal device has picture electrodes 13 on the bottom substrate 11 and picture electrodes 14 on the other substrate 12.

According to the invention a polymer structure 15 with pressure sensitive characteristics is provided between the picture electrodes 13, 14, which polymer structure

comprises in this example capsules 16 filled with liquid crystal material 17, comparable to PDLC.

A class of materials to be used for the polymer structure 15 is formed by the Quantum Tunnelling Composites (QTC). QTC is a polymer composite with conducting particles deposited in its structure. The conducting particles have dendrites. The particles are spaced apart and do not form a physical conduction path. Tensile or compressive strain on the material however brings the particles close to each other. The space separation of the particles is reduced by the presence of the dendrites. At a certain loading point, the space separation of the particles becomes close enough to enable the electrons from one particle to jump to the other particle through the dendrites. However, the dendrites from two different particles are still not in contact with each other. The quantum tunneling act of the electrons leads to rapid resistivity decrease of the material as a whole. This nonlinear behavior gives rise to a transition point that sharply changes the resistance of the material from  $10^{12}$  to  $10^{-1} \Omega$ .

Hence, QTC is a pressure/force sensitive switching material whose switching properties are comparable to these of a mechanical switch. Moreover it can be moulded into different shapes and can be mixed with other polymers. So in this example the pixel itself becomes intrinsically touch sensitive. This is represented in Figure 2 by means of the variable resistor 21.

A further example of an liquid crystal display device with polymer network is the so called Axially Symmetric Mode for wide viewing angle liquid crystal display devices and plasma addressed liquid crystal display devices, where pixels are individually encapsulated using a polymer network. Again, this polymer network could be provided with pressure dependent resistivity to enable touch sensing.

Figure 3 shows a part of an electrophoretic displays in which microcapsules 16 comprise an electrophoretic medium such as an electrophoretic liquid 18 in which positively charged particles 19 and negatively charged particles 20 are suspended. The polymer structure 15 with microcapsules 16 also is suitable for incorporating a QTC into the polymer network to make the pixel intrinsically touch sensitive. In this example, the polymer with pressure sensitive resistance replaces a binder if any, as possibly present in the example of Figure 2.

An advantage of applying the polymer with pressure dependent resistance to an electrophoretic display (or indeed any other display which is bistable under pressure – such as electrochromic displays) is that it is simple to directly determine the touch position

by measuring the resistance between row and column electrodes (passive driving) or between picture electrodes and a counter electrode (active driving). By touching the display, a short circuit is created, which will reduce the voltage across the pixel. In the case of bistable displays, this will not adversely effect the pixel performance (as would be the case in a display which is continuously driven), as there will in any case be no voltage across the pixel during its bistable period.

The protective scope of the invention is not limited to the embodiments described, while the invention is also applicable to other display devices, for example, electrochromic and electrowetting display pixels in which pixels are individually encapsulated using a polymer network. Here also, this polymer network could be provided with pressure dependent resistivity to enable touch sensing. The same applies to a display in which the polymer network forming the binder around the rotating balls with black and white hemispheres could be provided with pressure dependent resistivity to enable touch sensing

Alternatively, flexible substrates (synthetic material) may be used (wearable displays, wearable electronics).

In the monitoring different variations are possible too, e.g. monitoring a row of picture elements, a column of picture elements a block of picture elements.

The invention resides in each and every novel characteristic feature and each and every combination of characteristic features. Reference numerals in the claims do not limit their protective scope. Use of the verb "to comprise" and its conjugations does not exclude the presence of elements other than those stated in the claims. Use of the article "a" or "an" preceding an element does not exclude the presence of a plurality of such elements.

## CLAIMS:

1. A touch sensitive display device comprising an elastic structure with a multiple of picture elements and having means for applying driving voltages to said picture elements the elastic structure comprising touch sensitive elements, the touch sensitive display device having means for monitoring the electrical characteristics of said touch sensitive elements and sensing a change in said electrical characteristics.
2. A touch sensitive display device as claimed in Claim 1 in which the touch sensitive elements at least have a nonlinear resistive part.
3. A touch sensitive display device as claimed in Claim 1 in which the touch sensitive elements comprise quantum tunneling composites.
4. A touch sensitive display device as claimed in Claim 1 in which the means for monitoring the electrical characteristics of the touch sensitive elements comprise at least an electrode of a picture element.
5. A touch sensitive display device as claimed in Claim 1 in which the picture elements comprise at least one capsule containing an electro-optical medium.
6. A touch sensitive display device as claimed in Claim 1 the electro-optical medium being a liquid crystal, a guest host system or an electrophoretic medium.
7. A touch sensitive display device as claimed in Claim 1 or 4 in which the means for monitoring the electrical characteristics monitor the electrical characteristics of at least one row of picture elements.
8. A touch sensitive display device as claimed in Claim 1 or 4 in which the means for monitoring the electrical characteristics monitor the electrical characteristics of at least one column of picture elements.



9. A touch sensitive display device as claimed in Claim 1 or 4 in which the means for monitoring the electrical characteristics monitor the electrical characteristics of a block of picture elements.




FIG. 1




FIG. 2




FIG. 3

(19) World Intellectual Property  
Organization  
International Bureau



(43) International Publication Date  
12 February 2004 (12.02.2004)

PCT

(10) International Publication Number  
**WO 2004/013746 A3**

(51) International Patent Classification<sup>7</sup>: **G06F 3/033**,  
3/033, G02F 1/133

(21) International Application Number:  
PCT/IB2003/003243

(22) International Filing Date: 16 July 2003 (16.07.2003)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:  
02078156.3 1 August 2002 (01.08.2002) EP

(71) Applicant (for all designated States except US): **KONINKLIJKE PHILIPS ELECTRONICS N.V.** [NL/NL];  
Groenewoudseweg 1, NL-5621 BA Eindhoven (NL).

(72) Inventors; and

(75) Inventors/Applicants (for US only): **RAAP, Adriaan, Y.** [NL/NL]; Prof . Holstlaan 6, NL-5656 AA Eindhoven (NL). **JOHNSON, Mark, T.** [GB/NL]; Prof . Holstlaan 6, NL-5656 AA Eindhoven (NL). **DE BOER, Dirk, K., G.** [NL/NL]; Prof . Holstlaan 6, NL-5656 AA Eindhoven (NL).

(74) Agent: **RAAP, Adriaan, Y.**; Philips Intellectual Property & Standards, Prof. Holstlaan 6, NL-5656 AA Eindhoven (NL).

(81) Designated States (national): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.


(84) Designated States (regional): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

**Declaration under Rule 4.17:**

— as to applicant's entitlement to apply for and be granted a patent (Rule 4.17(ii)) for the following designations AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, UZ, VC, VN, YU, ZA, ZM, ZW, ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE,

[Continued on next page]

(54) Title: TOUCH SENSITIVE DISPLAY DEVICE



(57) Abstract: A touch-sensitive display is made by incorporating a pressure dependent resistive polymer composite into the polymer networks, which are components of the electro-optical pixels. Examples are PDLC, electrophoretic displays, polymer dispersed guest/host systems and other polymer dispersed LC devices.

WO 2004/013746 A3



DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT,  
RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM,  
GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG)

(88) Date of publication of the international search report:

14 October 2004

**Published:**

- with international search report
- before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments

*For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.*

# INTERNATIONAL SEARCH REPORT

International Application No

PCT/IB 03/03243

A. CLASSIFICATION OF SUBJECT MATTER  
IPC 7 G06F3/033 G06F3/033 G02F1/133

According to International Patent Classification (IPC) or to both national classification and IPC

## B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 7 G06F G02F

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

EPO-Internal, WPI Data, PAJ, IBM-TDB, COMPENDEX, INSPEC

## C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	US 4 814 760 A (JOHNSTON JAMES P ET AL) 21 March 1989 (1989-03-21) column 1, line 38 - column 3, line 12 column 4, line 4 - line 63 figures 1-4	1,4-9
X	EP 0 773 497 A (SYMBIOS LOGIC INC) 14 May 1997 (1997-05-14) column 1, line 56 - column 2, line 13 column 6, line 2 - line 11 column 6, line 57 - column 8, line 32 column 9, line 7 - column 11, line 50 claims 1-3 figures 1,3-5	1-9
	----- -/--	

☒ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

\* Special categories of cited documents:

\*A\* document defining the general state of the art which is not considered to be of particular relevance

\*E\* earlier document but published on or after the international filing date

\*L\* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

\*O\* document referring to an oral disclosure, use, exhibition or other means

\*P\* document published prior to the international filing date but later than the priority date claimed

\*T\* later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

\*X\* document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

\*Y\* document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

\*Z\* document member of the same patent family

Date of the actual completion of the international search

30 July 2004

Date of mailing of the international search report

05/08/2004

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2  
NL - 2280 HV Rijswijk  
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,  
Fax: (+31-70) 340-3016

Authorized officer

Butler, M

# INTERNATIONAL SEARCH REPORT

Int. onal Application No  
PCT/IB 03/03243

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT		
Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	<p>PATENT ABSTRACTS OF JAPAN vol. 2000, no. 20, 10 July 2001 (2001-07-10) -&amp; JP 2001 075074 A (INTERNATL BUSINESS MACH CORP &lt;IBM&gt;), 23 March 2001 (2001-03-23) abstract paragraph '0001! paragraph '0008! - paragraph '0010! paragraph '0015! paragraph '0022! - paragraph '0024! figures 3-8</p>	1-9
X	<p>US 5 949 501 A (IZUNO AKINOBU ET AL) 7 September 1999 (1999-09-07) column 2, line 9 - line 31 column 6, line 63 - column 7, line 46 column 8, line 41 - line 61 column 9, line 24 - column 10, line 20 figures 1-5</p>	1-9
X	<p>WO 01/02899 A (E INK CORP) 11 January 2001 (2001-01-11) page 3, line 6 - line 17 page 6, line 7 - page 8, line 12 page 10, line 6 - line 19 page 16, line 9 - line 24 figures 1-3</p>	1-9
A	<p>US 2002/025837 A1 (LEVY DAVID H) 28 February 2002 (2002-02-28) paragraph '0002! paragraph '0004! - paragraph '0006! paragraph '0129! paragraph '0135! figure 4</p>	2,3
A	<p>WO 01/88935 A (LEFTLY STEVEN ; JONES DIANNE (GB); LUSSEY DAVID (GB); PERATECH LTD (GB) 22 November 2001 (2001-11-22) page 2, line 12 - page 3, line 11 page 5, line 22 - page 6, line 8 page 8, line 8 - line 11 page 10, line 2 - line 15 page 11, line 3 - line 17 page 13, line 9 - page 14, line 3 figures 1-4</p>	2,3
A	<p>EP 0 829 748 A (SONY CORP) 18 March 1998 (1998-03-18) column 6, line 16 - column 7, line 49 figures 1,2</p>	6

# INTERNATIONAL SEARCH REPORT

International Application No

PCT/IB 03/03243

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
US 4814760	A	21-03-1989	AU 582181 B2	16-03-1989
			AU 4645085 A	03-07-1986
			CA 1254685 A1	23-05-1989
			DE 3584242 D1	31-10-1991
			EP 0189590 A2	06-08-1986
			JP 1889137 C	07-12-1994
			JP 6018031 B	09-03-1994
			JP 61157931 A	17-07-1986
EP 0773497	A	14-05-1997	US 5777596 A	07-07-1998
			DE 69614635 D1	27-09-2001
			DE 69614635 T2	07-02-2002
			EP 0773497 A1	14-05-1997
			JP 9274537 A	21-10-1997
JP 2001075074	A	23-03-2001	US 6501529 B1	31-12-2002
US 5949501	A	07-09-1999	JP 9282095 A	31-10-1997
WO 0102899	A	11-01-2001	AU 5779200 A	22-01-2001
			EP 1192504 A2	03-04-2002
			JP 2003504666 T	04-02-2003
			WO 0102899 A2	11-01-2001
			US 6392786 B1	21-05-2002
US 2002025837	A1	28-02-2002	AU 6478101 A	17-12-2001
			CA 2410454 A1	13-12-2001
			CN 1439164 T	27-08-2003
			EP 1290705 A2	12-03-2003
			JP 2003536307 T	02-12-2003
			WO 0195358 A2	13-12-2001
WO 0188935	A	22-11-2001	AU 5653101 A	26-11-2001
			CA 2407835 A1	22-11-2001
			CN 1429394 T	09-07-2003
			EP 1282906 A1	12-02-2003
			WO 0188935 A1	22-11-2001
			JP 2003533847 T	11-11-2003
EP 0829748	A	18-03-1998	JP 9146124 A	06-06-1997
			EP 0829748 A2	18-03-1998
			US 6016178 A	18-01-2000